119R-104180	REV.:3 8/12/20	SEE DET. 1-	REV.	DESCRIPT	ION	DATE	BY
		SEE DET. T					
					ALTERNAT TOP AND RUNNING TO EACH	BOTTOM PERPENI	OF PAD
2. TABLE IS AVE	FOR CUSTOMER REFERENCE. RAGE DESIGN DATA FOR REFERENCE. DOT BOTH SIDES LOCATED APPROX AS LENGTH AND WIDTH AVAILABLE CONTACT		ART NUMBER	SHEAR-FLEX BLACK	RATED COMPRESSIVE LOAD (PSI) 165	SHORE A DURO ±5 85	COLOR CODE RED
JOB NAME:	CERTIFIED FOR: MODEL SHEAR-FLEX 165 PSI. JOB NAME:			VMC	NONE Sheet:	n e Ivy ↓↓↓↓ ↓↓↓↓	SCMA
		18 x 18 NATURAL RUBBER		GROUP	DRAWING NO.:		REVISION
CUSTOMER P.O.: ELASTOMER		ELASTOMERIC PAD 3/8" INCH TH		THE POWER OF TOGETHER"	DIAWING NU.:		NE VISION
SALES ORDER:				Bloomingdale, NJ 07403 Houston, TX 77041			

PROPRIETARY: EXCEPT AS OTHERWISE AGREED IN WRITING, THE INFORMATION AND DESIGN DISCLOSED HEREIN ARE THE PROPERTY OF THE VMC GROUP AND MUST NOT BE COPIED OR DISTRIBUTED OUTSIDE THE VMC GROUP EXCEPT TO AUTHORIZED PERSONS WITH A GENUINE NEED TO KNOW WHO BY THE USE HEREOF ACKNOWLEDGE THE VMC GROUP'S OWNERSHIP AND AGREE TO MAINTAIN THIS INFORMATION AND DESIGN DISTRICT CONFIDENCE.