6R-103552 REV.: 2									REV.		DESCRIPTIO	N	DATE	Bì
				(<i>t</i> e	OVER	RALL LEN(-						
					KUUU				 . OF PART					
				C										
	"F" IN		GTH	RECOMMENDED	TOTAL TI	RAVEL	ALLOWABLE		FROM NEUTRAL	LENGTH	PRESSURE	DIMEN	ISIONS	
NOMINAL PIPE SIZE	"F" NEUTRAL LENGTH	MINIMUM INSTALLED	MAXIMUM	PIPE OPENING	TOTAL COMPRESSED	TOTAL EXTENDED	AXIAL COMPRESSION	AXIAL EXTENSION	+/- LATERAL DEFLECTION	+/- ANGULAR DEFLECTION	POSITIVE (PSIG)	"A" LENGTH OF FITTING	"B" LENGTH OF RUBBER	

	SIZE	"F" NEUTRAL	MINIMUM	MAXIMUM	PIPE	TOTAL	TOTAL	AXIAL	AXIAL	+/- LATERAL	+/- ANGULAR	POSITIVE	"A' LENGTH	"B" LENGTH
		LENGTH	INSTALLED	INSTALLED	OPENING	COMPRESSED	EXTENDED	COMPRESSION	EXTENSION	DEFLECTION	DEFLECTION	(PSIG)	OF FITTING	OF RUBBER
Г	3/4	8.0	7.340	8.110	6.250	7.130	8.230	0.870	0.230	0.870	32.2°	150	1.06	5.88
	1	8.0	7.340	8.110	6.250	7.130	8.230	0.870	0.230	0.870	25.3°	150	1.14	5.72
	1-1/4	8.0	7.340	8.110	6.250	7.130	8.230	0.870	0.230	0.870	20.7°	150	1.26	5.48
	1-1/2	8.0	7.340	8.110	6.050	7.130	8.230	0.870	0.230	0.870	17.5°	150	1.30	5.40
Г	2	8.0	7.340	8.110	6.250	7.130	8.230	0.870	0.230	0.870	13.3°	150	1.42	5.16
	2-1/2	8.0	7.340	8.110	6.250	7.130	8.230	0.870	0.230	0.870	10.7°	150	1.69	4.62
	3	8.0	7.340	8.110	6.250	7.130	8.230	0.870	0.230	0.870	8.9°	150	1.69	4.62

NOTES:

1) ALL DIMENSIONS IN INCHES.

2) PRESSURE: OPERATING - 150 PSI, BURST - 600PSI, VACUUM - 26 HG. HEAVYWEIGHT STYLE AVAILABLE.

3) PRESSURE RATING BASED ON 170 °F OPERATING TEMPERATURE.

4) MAXIMUM OPERATING TEMPERATURE 225 °F.

5) STANDARD NEOPRENE TUBE AND COVER. OTHER MATERIALS ARE AVAILABLE.

6) OTHER SIZES, TEMPERATURES, PRESSURES, AND LENGTHS AVAILABLE.

7) COMPOJNDS OR FINISHES WITH EQUAL OR SUPERIOR PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE.

8) REFER TO DRAWING II-5214 FOR INSTALLATION INSTRUCTIONS.

OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIOR PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE. WARNING: EXPANSION JOINTS MAY OPERATE IN PIPELINES OR EQUIPMENT CARRYING FLUIDS AND/OR GASES AT ELEVATED TEMPERATURES AND PRESSURES. NORMAL PRECAUTIONS SHOULD BE TAKEN TO MAKE SURE THESE PARTS ARE INSTALLED CORRECTLY AND INSPECTED REGULARLY. PRECAUTIONS SHOULD BE TAKEN TO PROTECT PERSONNEL IN THE EVENT OF LEAKAGE OR SPLASH.

CERTIFIED FOR:			SCALE :		
			NONE	Memž	
JOB NAME:			0.117.777		
	MODEL 2655 RUBBER EXPENSION JOINT		SHEET:	····- VIS	
CUSTOMER :					
	DOUBLE SPHERE				REVISION
CUSTOMER P.O.			DRAWING NO.:		REVISION
		The Power of Together Bloomingdale, NJ 07403			
SALES ORDER:		Houston, TX 77041			

PROPRIETARY: EXCEPT AS OTHERWISE AGREED IN WRITING, THE INFORMATION AND DESIGN DISCLOSED HEREIN ARE THE PROPERTY OF THE VMC GROUP AND MUST NOT BE COPIED OR DISTRIBUTED OUTSIDE THE VMC GROUP EXCEPT TO AUTHORIZED PERSONS WITH A GENUINE NEED TO KNOW WHO BY THE USE HEREOF ACKNOWLEDGE THE VMC GROUP'S OWNERSHIP AND AGREE TO MAINTAIN THIS INFORMATION AND DESIGN IN STRICT CONFIDENCE.