


REV.	DESCRIPTION	DATE	BY



**MATERIAL:**  
 HOSE - BRONZE  
 BRAID - BRONZE  
 MALE FITTINGS - WROUGHT COPPER

- NOTES:**
1. INSTALL CONNECTOR IN A STRAIGHT LINE WITHOUT OFFSET. PIPING TO BE SUPPORTED SO THAT CONNECTOR DOES NOT CARRY PIPE LOAD.
  2. INSTALL IN LINE WITHOUT TWISTING CONNECTOR.
  3. 2" I.D. AND LARGER ARE DOUBLE BRAIDED FOR EXTRA STRENGTH AND PROTECTION.

TO FIT COPPER TUBE		FLEXIBLE TUBING	DIMENSIONS (IN)				MAX. W.P. @70°F (PSI)
ACTUAL O.D.	NOMINAL O.D.	I.D.	H (+/- 1/4)	A (MAX.)	B (MAX.)	E (+/- 1/8)	
1/4	1/8	1/4	7-1/2	9/16	5/8	1/2	450
3/8	1/4	5/16	8-1/4	11/16	3/4	5/8	450
1/2	3/8	3/8	9	3/4	7/8	3/4	450
5/8	1/2	1/2	9-3/4	1	1-1/8	7/8	450
3/4	5/8	1/2	10	1	1-1/8	1	450
3/4	5/8	3/4	11-1/4	1-3/8	1-1/2	1-1/8	440
7/8	3/4	3/4	11-1/2	1-3/8	1-1/2	1-1/4	440
1-1/8	1	1	13	1-5/8	1-7/8	1-1/2	400
1-3/8	1-1/4	1-1/4	14-3/4	2-1/8	2-1/8	1-5/8	480
1-5/8	1-1/2	1-1/2	17	2-1/4	2-3/8	2	420
2-1/8	2	2	20	3-1/8	3-1/4	2-1/2	190

OTHER MATERIALS, COMPOUNDS OR FINISHES WITH EQUAL OR SUPERIOR PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE.

<b>CERTIFIED FOR:</b> JOB NAME: _____ CUSTOMER : _____ CUSTOMER P.O.: _____ SALES ORDER: _____	<b>MODEL BR-FS METAL-FLEX FREON FLEXIBLE CONNECTORS</b>	 <b>THE VMC GROUP</b> <i>The Power of Together</i> Bloomingdale, NJ 07403 Houston, TX 77041	SCALE : NONE		
			SHEET:		
			DRAWING NO.:		REVISION
			_____		_____