119R-103752 REV.: 1 REV. DESCRIPTION DATE BY LOAD Vs. DEFLECTION 2500 2400 3/8" 1/8" 15/64" 2300 2200 2100 2000 1900 1800 1700 LOAD, POUNDS PER SQ. INCH 1600 1500 1400 1300 1200 1100 1000 900 800 700 W 600 500 400 300 200 100 .020 .040 .060 .080 .100 .120 .140 .160 .180 DEFLECTION, INCHES (2" x 2" PAD) NOTES: 1. CONTACT VMC MANUFACTURING, SOLD IN SIZES AS PER CUSTOMER REQUIREMENT 2. STANDARD THICKNESS RANGES FROM .125 TO 1 INCH. 3. CUSTOM CUT LENGTH & WIDTH AVAILABLE CONTACT VMC FOR AVAILABILITY. OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIOR PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE. SCALE: **CERTIFIED FOR:** NONE JOB NAME: _ SHEET: MODEL FABRI-FLEX REINFORCED DUCK CUSTOMER: **ISOLATION PAD** THE VMC GROUP DRAWING NO. REVISION CUSTOMER P.O.: The Power of Together

SALES ORDER:

Bloomingdale, NJ 07403

Houston, TX 77041