


REV.	DESCRIPTION	DATE	BY

TYPE HS-2E PRE-COMPRESSED SPRING HANGERS					
FOR 2" NOMINAL DEFLECTION					
HANGER	RATED LOAD	DEFLECTION	SPRING RATE	SPRING	
HANGER	(LBS)	(IN)	(LB/IN)	COLOR CODE	
HS-2E-80PR	80	2.00	40	BLACK	
HS-2E-150PR	150	2.00	75	GREEN	
HS-2E-300PR	300	2.00	150	DK YELLOW	
HS-2E-500PR	500	2.00	250	BLUE	
HS-2E-776N <sup>1</sup> PR	776	2.00	388	BLUE/BLACK	
HS-2E-1000PR	1000	2.00	500	TAN	
HS-2E-1400PR	1400	1.87	749	RED	
HS-2E-1600N <sup>1</sup> PR	1600	2.13	750	TAN/RED	
HS-2E-1800PR	1800	1.71	1053	DK GRAY	
HS-2E-2050PR	2050	1.64	1250	DK BLUE	
HS-2E-2250N <sup>1</sup> PR	2250	1.62	1389	DK BLUE/BLACK	
HS-2E-2460N <sup>1</sup> PR	2460	1.64	1500	DK BLUE/RED	
HS-2E-2700N <sup>1</sup> PR	2700	1.64	1646	DK BLUE/ DK GREEN	

## NOTES:

1. TWO NESTED SPRINGS YIELD THIS LOAD. THE COLOR CODE INDICATED IS FOR OUTER SPRING/ INNER SPRING.



## NOTES:

SALES ORDER:

- 1. HANGER RODS, NUTS AND WASHERS, AS SHOWN, NOT BY THE VMC GROUP. INSTALL WASHER .16 THK. MIN. X 3 O.D. MIN WITH REQUIRED INSIDE DIAMETER TO ACCOMMODATE ROD SIZE IN USE. THIS CAN BE ACCOMPLISHED BY USING A SINGLE WASHER OR BY STACKING NOT MORE THAN TWO WASHERS.
- 2. STANDARD FINISH: HANGER BOX PAINTED, POWDER COATED OR GALVANIZED STEEL, SPRING POWDER COAT.
- 3. SEISMIC VERTICAL LIMIT-STOP REQUIRED FOR SEISMIC APPLICATIONS.
- 4. ALL DIMENSIONS IN INCHES, INTERPRET PER ANSI Y14.
- 5. ALL DIMENSIONS ARE FOR REFERENCE, DIMENSIONS SHOWN AS NOMINAL.
- 6. ALL SPRINGS ARE DESIGNED WITH MINIMUM 50% OVER-TRAVEL.
- 7. HANGER BOXES ARE AVAILABLE PRE-COMPRESSED UP TO THEIR DESIGNATED MAX. LOAD. PERCENTAGE OF PRE-COMPRESSION TO BE DETERMINED BY ENGINEERED APPLICATION OR AS REQUESTED BY CUSTOMER. CONSULT FACTORY FOR POSSIBLE ADDITIONAL PARAMETERS AND OR LIMITATIONS.

8. RATED DEFLECTIONS ARE WITHIN 25% OF NOMINAL. HIGHER DEFLECTIONS ARE ALLOWED IF THEY MEET SPECIFICATIONS.

ISOLATOR SELECTIONS		
OC 1:	LOC 2:	
OC 3:	LOC 4:	
OC 5:	LOC 6:	
OC 7:	LOC 8:	
CUSTOMER EQP'T. TAG:		

NOTE: MATERIAL SHOWN IS FOR (1) SET.

OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIOR PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE.

CERTIFIED FOR:		
JOB NAME:		
CUSTOMER:		
CUSTOMER P.O.:		

MODEL HS-2E 80-2700 LBS. PRE-COMPRESSED SPRING HANGERS 2 INCH DEFLECTION

	SH
THE VMC GROUP	DF
The Power of Together	
Bloomingdale, NJ 07403	
Houston, TX 77041	

SCALE : NONE	Wempe'
SHEET:	`··· <del>·VISCMA</del>

RAWING NO. REVISION