
213R-103603 REV.: 2 DESCRIPTION DATE BY REV.



BOLT HOLES FURNISHED

■ NO

PIPE CLAMP (BY OTHERS) * CONTRACTOR TO ADVISE WHEN RELEASING ORDER IF BOLT PROJECTION IS OTHER THAN FREE HEIGHT SHOWN. "E" O.D. BY "F" FREE LENGTH OF SPRING -ANCHOR BOLT (BY OTHERS) CONCRETE SLAB -RIBBED ELASTOMERIC PAD INSULATION

ISOLATOR	BASE PLATE			ISOLATOR			
DESIGNATION	Α	В	С	D	E	F	G
SWX-1A	5	4	3-1/2	3-1/2	2	2-1/2	3/8
SWX-1	6-1/4	4	4-3/4	6	3-1/4	4	5/8
SWX-2	7	4	5-1/2	8	4	6	5/8
SWX-3A	7	4	5-1/2	7-1/2	4	6	5/8
SWX-3B	8	5	6-1/2	10	5	8	3/4
SWX-3C	9	6	7-1/2	11-1/4	6	9	1
SWX-4.5A	9	6	7-1/2	11	6	9	3/4
SWX-4.5B	11	8	9-1/2	12-1/2	8	10	1
SWX-6A	11	8	9-1/2	14	7-1/2	12	1
SWX-6B	11	8	9-1/2	15-1/4	8	13	1
SWCX-1-2100	10	6	8-1/2	12-1/8	5-1/2	10-1/4	3/4
SWCX-1-2800	10	6	8-1/2	11-3/4	5-1/2	9-5/8	7/8
SWCX-1-4000	10	6	8-1/2	11-3/4	5-1/2	9-5/8	7/8
SWCX-1-4100	10	6	8-1/2	11-3/8	5-1/2	9-1/16	7/8
SWCX-1-5800	10	6	8-1/2	11-3/8	5-1/2	9-1/16	7/8
SWCX-1-9400	10	6	8-1/2	11	5-1/2	8-1/4	1-1/4
SWCX-1-12500	10	6	8-1/2	11-1/8	5-1/2	8-1/4	1-1/4
SWCX-2-4200	10	6	8-1/2	12-1/2	5-1/2	10-1/4	1
SWCX-2-5600	10	6	8-1/2	12-1/8	5-1/2	9-5/8	1
SWCX-2-6400	10	6	8-1/2	12-5/8	5-1/2	10-1/4	1
SWCX-2-8000	10	6	8-1/2	12-1/4	5-1/2	9-5/8	1
SWCX-3-6300	10	6	8-1/2	12-7/8	5-1/2	10-1/4	1-1/4
SWCX-3-9600	10	6	8-1/2	13	5-1/2	10-1/4	1-1/4

NOTES:

- 1) ALL DIMENSIONS ARE IN INCHES.
- 2) REFER TO DRAWINGS II-2311 AND II-2312 FOR INSTALLATION INSTRUCTIONS.
- 2) FINISH INDUSTRIAL GRADE ENAMEL.

OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIOR PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE.

CERTIFIED FOR:				
JOB NAME:				
CUSTOMER:				
CUSTOMER P.O.:				

SALES ORDER:

BASE PLATE DETAIL

MODEL SW SERIES ISOLATED RISER SUPPORT

		s
	THE VMC GROUP	D
	The Power of Together	
ı	Bloomingdale, NJ 07403	
ı	Houston, TX 77041	

SCALE : NONE	10.
SHEET:	``,,'` <u>`</u>

RAWING NO.:

REVISION