


REV.	DESCRIPTION	DATE	BY

TYPE HRSA-3C PRE-COMPRESSED ELASTOMERIC & SPRING ANGULARITY HANGERS FOR 3" NOMINAL DEFLECTION					
HANGER	RATED LOAD (LBS)	DEFLECTION (IN)	SPRING RATE (LBS/IN)	SPRING COLOR CODE	ELEMENT LOAD & COLOR CODE
HRSA-3C-75PR	75	3.10	25	WHITE	RE-C-380 BLACK
HRSA-3C-145PR	145	3.09	50	LT PURPLE	RE-C-380 BLACK
HRSA-3C-215PR	215	2.87	83	LT BROWN	RE-C-380 BLACK
HRSA-3C-315PR	315	2.78	133	ORANGE	RE-C-380 BLACK
HRSA-3C-470PR	470	2.80	200	DK BROWN	RE-C-520 RED
HRSA-3C-600PR	600	2.60	267	DK PURPLE	RE-C-840 GREEN



ISOLATOR SELECTIONS			
LOC 1:	LOC 2:		
LOC 3:	LOC 4:		
LOC 5:	LOC 6:		
LOC 7:	LOC 8:		
CUSTOMER EQP'T. TAG:			

NOTE: MATERIAL SHOWN IS FOR (1) SET.

NO	NOTES:		
1.	1. HANGER RODS, NUTS AND WASHERS, AS	SHOWN, NOT BY THE VMC GROUP. INSTALL WASHER .16 THK. MIN. X 2-7/8 O.D.	MIN. WITH
	REQUIRED INSIDE DIAMETER TO ACCOMM	MODATE ROD SIZE IN USE. THIS CAN BE ACCOMPLISHED BY USING A SINGLE WA	SHER OR
	BY STACKING NOT MORE THAN TWO WASH	SHERS.	
2.	2 STANDARD FINISH: HANGER BOX - PAINTE	ED. POWDER COATED OR GALVANIZED STEEL, SPRING - POWDER COAT	

- 3. SEISMIC VERTICAL LIMIT-STOP HARDWARE REQUIRED FOR SEISMIC APPLICATIONS
- 4. .ALL DIMENSIONS IN INCHES. INTERPRET PER ANSI Y14.
- 5. ALL DIMENSIONS ARE FOR REFERENCE, DIMENSIONS SHOWN AS NOMINAL.
- 6. ALL SPRINGS ARE DESIGNED WITH MINIMUM 50% OVER-TRAVEL.
- 7. HANGER BOXES ARE AVAILABLE PRE-COMPRESSED UP TO THEIR DESIGNATED MAX. LOAD. PERCENTAGE OF PRE-COMPRESSION TO BE DETERMINED BY ENGINEERED APPLICATION OR AS REQUESTED BY CUSTOMER. CONSULT FACTORY FOR POSSIBLE ADDITIONAL PARAMETERS AND OR LIMITATIONS.
- 8. HANGER BOXES WITH AN ELASTOMERIC ELEMENT HAVE UP TO AN ADDITIONAL 1/2" NOMINAL DEFLECTION.
- 9. DOUBLE LOWER NUT PROVIDED.
- 10. ROD EXTENSION BELOW LOWER NUT EXTENDS (1.5XROD DIA.) AS SHIPPED.
- 11. PRE-COMPRESSED 50% OF SPRING RATED DEFLECTION.
- 12. RATED DEFLECTIONS ARE WITHIN 25% OF NOMINAL. HIGHER DEFLECTIONS ARE ALLOWED IF THEY MEET SPECIFICATIONS.

OTHER MATERIALS.	COMPOUNDS.	OR FINISHES	WITH EQUAL	OR SUPERIO
PROPERTIES MAY F	RE SUBSTITUTE	D AS THEY BE	COME AVAIL	ARI F

CERTIFIED FOR:	MODEL HRSA-3C 75-600 LBS.		SCALE : NONE	<del>-</del>
JOB NAME:	PRE-COMPRESSED		SHEET:	Membe,
CUSTOMER:	ELASTOMERIC AND SPRING ANGULARITY		1 OF 1	
CUSTOMER P.O.:	HANGERS	THE VMC GROUP The Power of Together	DRAWING NO.:	REVISION
SALES ORDER:	3 INCH DEFLECTION	Bloomingdale, NJ 07403 Houston, TX 77041		