

NOTES:

- 1. HANGER RODS, NUTS AND WASHERS, AS SHOWN. NOT BY THE VMC GROUP.
- 2. STANDARD FINISH: HANGER BOX PAINTED, POWDER COATED OR GALVANIZED STEEL, SPRING POWDER COAT.
- 3. SEISMIC VERTICAL LIMIT-STOP REQUIRED FOR SEISMIC APPLICATIONS, NOT BY THE VMC GROUP. INSTALL WASHER 1/4 THK. MIN. X 3-1/2 O.D. MIN. WITH REQUIRED INSIDE DIAMETER TO ACCOMMODATE ROD SIZE IN USE. THIS CAN BE ACCOMPLISHED BY USING A SINGLE WASHER OR BY STACKING NOT MORE THAN TWO WASHERS.
- 4. ALL DIMENSIONS IN INCHES, INTERPRET PER ANSI Y14.

(6.1/4)

FREE HEIGHT

3/8 OPERATING


GAP

- 5. ALL DIMENSIONS ARE FOR REFERENCE, DIMENSIONS SHOWN AS NOMINAL.
- 6. ALL SPRINGS ARE DESIGNED WITH MINIMUM 50% OVER-TRAVEL.
- 7. HANGER BOXES WITH AN ELASTOMERIC ELEMENT HAVE UP TO AN ADDITIONAL 1/2" NOMINAL DEFLECTION.
- 8. RATED DEFLECTIONS ARE WITHIN 25% OF NOMINAL. HIGHER DEFLECTIONS ARE ALLOWED IF THEY MEET SPECIFICATIONS

(2) SPRING CUPS

SEISMIC VERTICAL LIMIT-STOP, NUT AND WASHER, TIGHTEN

TOGETHER (SEE NOTE 3)



ISOLATOR SELECTIONS			
LOC 1:	LOC 2:		
LOC 3:	LOC 4:		
LOC 5:	LOC 6:		
LOC 7:	LOC 8:		
CUSTOMER EQP'T. TAG:			

NOTE: MATERIAL SHOWN IS FOR (1) SET.

OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIOR PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE.

CERTIFIED FOR:			SCALE : NONE		
JOB NAME:	MODEL H2RSPA-1E 2800-6500 LBS. DOUBLE		SHEET:	Memb	
CUSTOMER:	ELASTOMERIC AND SPRING ANGULARITY				
CUSTOMER P.O.:	HANGERS	THE VMC GROUP The Power of Together	DRAWING NO.:		REVISION
SALES ORDER:	1 INCH DELFECTION	Bloomingdale, NJ 07403 Houston, TX 77041			