


DESCRIPTION REV. DATE BY

TYPE HRS-1B ELASTOMERIC & SPRING HANGERS FOR 1" NOMINAL DEFLECTION					
HANGER	RATED LOAD (LBS)	DEFLECTION (IN)	SPRING RATE (LB/IN)	SPRING COLOR CODE	ELEMENT LOAD & COLOR CODE
HRS-1B-20	20	1.48	16	DK BLUE	RE-A-35 BLUE
HRS-1B-35	35	1.57	30	BLACK	RE-A-35 BLUE
HRS-1B-50	50	1.38	45	RED	RE-A-75 RED
HRS-1B-70	70	1.25	80	DK GREEN	RE-A-75 RED
HRS-1B-85	85	1.09	105	GRAY	RE-A-120 GREEN



	2	4	6	8
ISOLATOR SELECTIONS				
LOC 1:	LOC 2:			

ISOLATOR SELECTIONS		
LOC 1:	LOC 2:	
LOC 3:	LOC 4:	
LOC 5:	LOC 6:	
LOC 7:	LOC 8:	
CUSTOMER EQP'T. TAG:		

NOTE: MATERIAL SHOWN IS FOR (1) SET.

5. ALL DIMENSIONS ARE FOR REFERENCE, DIMENSIONS SHOWN AS NOMINAL.

6. ALL SPRINGS ARE DESIGNED WITH MIN IMUM 50% OVER-TRAVEL.

4. ALL DIMENSIONS IN INCHES. INTERPRET PER ANSI Y14.

7. HANGER BOXES ARE AVAILABLE PRE-COMPRESSED UP TO THEIR DESIGNATED MAX. LOAD. PERCENTAGE OF PRE-COMPRESSION TO BE DETERMINED BY ENGINEERED APPLICATION OR AS REQUESTED BY CUSTOMER. CONSULT FACTORY FOR POSSIBLE ADDITIONAL PARAMETERS AND OR LIMITATIONS.

3. SEISMIC VERTICAL LIMIT-STOP HARDWARE REQUIRED FOR SEISMIC APPLICATIONS, NOT BY THE VMC GROUP. INSTALL WASHER .1 THK. MIN. X 1-1/4 O.D. MIN. WITH REQUIRED INSIDE DIAMETER TO ACCOMMODATE ROD SIZE IN USE, THIS CAN BE ACCOMPLISHED BY USING A SINGLE WASHER OR BY STACKING NOT MORE THAN TWO

8. HANGER BOXES WITH AN ELASTOMERIC ELEMENT HAVE UP TO AN ADDITIONAL 1/2" NOMINAL DEFLECTION

9. RATED DEFLECTIONS ARE WITHIN 25% OF NOMINAL, HIGHER DEFLECTIONS ARE ALLOWED IF THEY MEET SPECIFICATIONS.

OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIO
PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE

CERTIFIED FOR:	
JOB NAME:	
CUSTOMER:	
CUSTOMER P.O.:	

SPRING - POWDER COAT.

WASHERS.

SALES ORDER:

MODEL HRS-1B 20-85 LBS. **ELASTOMERIC AND SPRING HANGERS** 1 INCH DEFLECTION

	NONE SHEET:	Membe,	
THE VMC GROUP The Power of Together Bloomingdale, NJ 07403 Houston, TX 77041	DRAWING NO.:		REVISION