

REV.	DESCRIPTION	DATE	BY	

TYPE HS-1C SPRING HANGERS FOR 1" NOMINAL DEFLECTION				
HANGER	RATED LOAD (LBS)	DEFLECTION (IN)	SPRING RATE (LBS/IN)	SPRING COLOR CODE
HS-1C-50	50	1.00	50	BLUE
HS-1C-100	100	1.00	100	TAN
HS-1C-150	150	1.00	150	RED
HS-1C-250	250	0.83	300	BLACK
HS-1C-300	300	0.75	400	DK YELLOW
HS-1C-370	370	0.75	493	YELLOW

1	3	5	7
(2)	4	6	8

N	NOTES:				
1.	HANGER RODS, NUTS AND WASHERS, AS SHOWN, NOT BY THE VMC GROUP.				
2.	STANDARD FINISH: HANGER BOX - PAINTED, POWDER COATED OR GALVANIZED STEEL,				
	SPRING - POWDER COAT.				

- 3. SEISMIC VERTICAL LIMIT-STOP REQUIRED FOR SEISMIC APPLICATIONS. NOT BY THE VMC GROUP. INSTALL WASHER .134 THK. MIN. X 1-3/4 O.D. MIN WITH REQUIRED INSIDE DIAMETER TO ACCOMMODATE ROD SIZE IN USE. THIS CAN BE ACCOMPLISHED BY USING A SINGLE WASHER OR BY STACKING NOT MORE THAN TWO WASHERS.
- 4. ALL DIMENSIONS IN INCHES, INTERPRET PER ANSI Y14.
- 5. ALL DIMENSIONS ARE FOR REFERENCE, DIMENSIONS SHOWN AS NOMINAL.
- 6. ALL SPRINGS ARE DESIGNED WITH MINIMUM 50% OVER-TRAVEL.
- 7. HANGER BOXES ARE AVAILABLE PRE-COMPRESSED UP TO THEIR DESIGNATED MAX. LOAD. PERCENTAGE OF PRE-COMPRESSION TO BE DETERMINED BY ENGINEERED APPLICATION OR AS REQUESTED BY CUSTOMER. CONSULT FACTORY FOR POSSIBLE ADDITIONAL PARAMETERS AND OR LIMITATIONS.

8. RATED DEFLECTIONS ARE WITHIN 25% OF NOMINAL, HIGHER DEFLECTIONS ARE ALLOWED IF THEY MEET SPECIFICATIONS.

ISOLATOR SELECTIONS		
LOC 1:	LOC 2:	
LOC 3:	LOC 4:	
LOC 5:	LOC 6:	
LOC 7:	LOC 8:	
CUSTOMER EQP'T. TAG:		

NOTE: MATERIAL SHOWN IS FOR (1) SET.

OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIOR PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE.

CERTIFIED FOR:		
JOB NAME:		
CUSTOMER:		
CUSTOMER P.O.:		

SALES ORDER:

MODEL HS-1C 50-370 LBS. SPRING HANGERS 1 INCH DEFLECTION

	SI
THE VMC GROUP	DF
The Power of Together	1

Houston, TX 77041

NONE IEET:

RAWING NO.: REVISION