

TYPE HS-2D SPRING HANGERS									
FOR 2" NOMINAL DEFLECTION									
HANGER	RATED LOAD	DEFLECTION	SPRING RATE	SPRING COLOR CODE					
	(LBS)	(IN)	(LB/IN)	SPRING COLOR CODE					
HS-2D-75	75	2.42	31	WHITE					
HS-2D-160	160	2.29	70	YELLOW					
HS-2D-230	230	2.30	100	GREEN					
HS-2D-355	355	2.15	165	DK BROWN					
HS-2D-435	435	1.89	230	RED					
HS-2D-600N ¹	600	1.88	319	RED/ BLACK					
HS-2D-725	725	1.61	450	TAN					
HS-2D-845	845	1.48	570	PINK					

DESCRIPTION

DATE

BY

REV.

1000

1320

NOTES:


HS-2D-1000N¹

HS-2D-1320N1

1. TWO NESTED SPRINGS YIELD THIS LOAD. THE COLOR CODE INDICATED IS FOR OUTER SPRING/ INNER SPRING

1.69

1.54



592

857

PINK/ BLACK

PINK/GRAY

ISOLATOR SELECTIONS				
LOC 1:	LOC 2:			
LOC 3:	LOC 4:			
LOC 5:	LOC 6:			
LOC 7:	LOC 8:			
CUSTOMER EQP'T. TAG:	•			

NOTE: MATERIAL SHOWN IS FOR (1) SET.

4. ALL DIMENSIONS IN INCHES, INTERPRET PER ANSI Y14.

SPRING - POWDER COAT.

THAN TWO WASHERS.

- 5. ALL DIMENSIONS ARE FOR REFERENCE, DIMENSIONS SHOWN AS NOMINAL.
- 6. ALL SPRINGS ARE DESIGNED WITH MINIMUM 50% OVER-TRAVEL.
- 7. HANGER BOXES ARE AVAILABLE PRE-COMPRESSED UP TO THEIR DESIGNATED MAX. LOAD. PERCENTAGE OF PRE-COMPRESSION TO BE DETERMINED BY ENGINEERED APPLICATION OR AS REQUESTED BY CUSTOMER, CONSULT FACTORY FOR POSSIBLE ADDITIONAL PARAMETERS AND OR LIMITATIONS

3. SEISMIC VERTICAL LIMIT-STOP REQUIRED FOR SEISMIC APPLICATIONS. NOT BY THE VMC GROUP. INSTALL WASHER .134 THK. MIN. X 2 O.D. MIN WITH REQUIRED INSIDE DIAMETER TO ACCOMMODATE ROD SIZE IN USE. THIS CAN BE ACCOMPLISHED BY USING A SINGLE WASHER OR BY STACKING NOT MORE

8. RA

TED DEFLECTIONS ARE WITHIN 25% OF NOMINAL. HIGHE	OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIOR PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE.			
TIEIEN EOD:			SCALE:	

ERTIFIED FOR:			SCALE : NONE	Memb	
USTOMER :	MODEL HS-2D 75-1320 LBS. SPRING HANGERS		SHEET:	`'· -V S(MA
USTOMER P.O.:	2 INCH DEFLECTION	THE VMC GROUP The Power of Together Bloomingdale, NJ 07403 Houston. TX 77041	DRAWING NO.:		REVISION