

TYPE HS-3C SPRING HANGERS						
FOR 3" NOMINAL DEFLECTION						
HANGER	RATED LOAD	DEFLECTION	SPRING RATE	SPRING		
	(LBS)	(IN)	(LB/IN)	COLOR CODE		
HS-3C-75	75	3.00	25	WHITE		
HS-3C-145	145	2.90	50	LT PURPLE		
HS-3C-215	215	2.59	83	LT BROWN		
HS-3C-315	315	2.37	133	ORANGE		
HS-3C-470	470	2.35	200	DK BROWN		

DESCRIPTION

DATE

DK PURPLE

ORANGE/RED

DK BROWN/RED

DK PURPLE/RED

BY

REV.

600

860

1055

1165

NOTES:

HS-3C-600

HS-3C-860N1

HS-3C-1055N1

HS-3C-1165N¹


1. TWO NESTED SPRINGS YIELD THIS LOAD. THE COLOR CODE INDICATED IS FOR OUTER SPRING/ INNER SPRING.

2.25

2.25

2.34

2.25



267

383

450

517

ISOLATOR SELECTIONS			
LOC 1:	LOC 2:		
LOC 3:	LOC 4:		
LOC 5:	LOC 6:		
LOC 7:	LOC 8:		
CUSTOMER EQP'T. TAG:			

NOTE: MATERIAL SHOWN IS FOR (1) SET.

4. ALL DIMENSIONS IN INCHES. INTERPRET PER ANSI Y14.

5. ALL DIMENSIONS ARE FOR REFERENCE, DIMENSIONS SHOWN AS NOMINAL.

6. ALL SPRINGS ARE DESIGNED WITH MINIMUM 50% OVER-TRAVEL.

7. HANGER BOXES ARE AVAILABLE PRE-COMPRESSED UP TO THEIR DESIGNATED MAX. LOAD. PERCENTAGE OF PRE-COMPRESSION TO BE DETERMINED BY ENGINEERED APPLICATION OR AS REQUESTED BY CUSTOMER. CONSULT FACTORY FOR POSSIBLE ADDITIONAL PARAMETERS AND OR LIMITATIONS.

3. SEISMIC VERTICAL LIMIT-STOP REQUIRED FOR SEISMIC APPLICATIONS. NOT BY THE VMC GROUP. INSTALL WASHER .16 THK. MIN. X 2-7/8 O.D. MIN WITH REQUIRED INSIDE DIAMETER TO ACCOMMODATE ROD SIZE IN USE. THIS CAN BE ACCOMPLISHED BY USING A SINGLE WASHER OR BY STACKING NOT MORE

8. RATED DEFLECTIONS ARE WITHIN 25% OF NOMINAL, HIGHER DEFLECTIONS ARE ALLOWED IF THEY MEET SPECIFICATIONS.

CERTIFIED FOR:

CUSTOMER P.O.:

SALES ORDER:

THAN TWO WASHERS).

JOB NAME: CUSTOMER:

MODEL HS-3C 75-1165 LBS. SPRING HANGERS 3 INCH DEFLECTION



NONE	Membe,
EET:	VISCMA

OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIOR PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE.

REVISION