161R-103535 REV.: 2 DESCRIPTION REV. DATE BY FUNCTION: USED IN AREAS WHICH MAY HAVE TO BE ISOLATED FROM THE OTHER PARTS OF THE BUILDING; SUCH AS MECHANICAL EQUIPMENT ROOMS, STUDIOS, MUSIC ROOMS, LABORATORIES AND DATA PROCESSING AREAS. NOTE: DIMENSIONS SHOWN IN PARENTHESES ARE IN -6" (I50) DIA---MILLIMETERS. PART NUMBER DESCRIPTION 801698 CAULKED 4" DRAIN . . . . . . . . 801698-01 THREADED 4" DRAIN . FLOATING SLAB 5" (125) MIN 8" (205) MAX NEOPRENE GASKETS PRESS FIT ISOLATION (30-40 DUROMETER) AIR GAP PANEL -SEEPAGE HOLES (WHEN SPECIFIED) STRUCTURAL SLAB 4 3/4" 6" (150)-COLLAR CAN BE USED AS FLASHING CLAMP WHEN REQUIRED POLISHED BRONZE TOP-PB 6" (I50) FOR INSIDE CAULK, — 4" DRAIN DIA <del>- -</del> | NO-HUB & SPEEDI-SET REGULARLY FURNISHED: −9 3/4" (250) DIA*-*--CAST IRON LOWER BODY AND CAULKED THREADED -OUTLET FLASHING COLLAR, ADJUSTABLE FERRULE AND FRAME WITH POLISHED BRONZE TOP. -12" (305) DIA-BRONZE CLEANOUT PLUG IN FERRULE AND NEOPRENE ISOLATION GASKET. OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIOR PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE. SCALE: **CERTIFIED FOR:** NONE JOB NAME: \_\_ SHEET: MODEL PMD-FF ISOLATED 4 INCH DRAIN CUSTOMER:\_\_\_\_ FOR FLOATING FLOOR THE VMC GROUP DRAWING NO. REVISION CUSTOMER P.O.: The Power of Together Bloomingdale, NJ 07403 SALES ORDER: Houston, TX 77041