161R-103536 REV.: 2 DESCRIPTION REV. DATE BY FUNCTION: USED IN AREAS WHICH MAY HAVE TO BE ISOLATED FROM THE OTHER PARTS OF THE BUILDING; SUCH AS MECHANICAL EQUIPMENT ROOMS, STUDIOS, MUSIC ROOMS, LABORATORIES AND DATA PROCESSING AREAS. -8 1/2" (215) DIA---NOTE: DIMENSIONS SHOWN IN PARENTHESES ARE IN PART NUMBER DESCRIPTION MILLIMETERS. 801697 CAULKED 6" DRAIN 801697-01 THREADED 6" DRAIN FLOATING 7" (125) MIN 8" (205) MAX NEOPRENE GASKETS PRESS FIT (30-40 DUROMETER) AIR GAP -SEEPAGE HOLES STRUCTURAL SLAB (120) 6" (150)COLLAR CAN BE USED AS FLASHING CLAMP WHEN REQUIRED POLISHED BRONZE TOP-PB 6" (I50) FOR INSIDE CAULK, -6" DRAIN DIA-NO-HUB & SPEEDI-SET REGULARLY FURNISHED: -9 3/4" (250) DIA-CAST IRON LOWER BODY AND -CAULKED FLASHING COLLAR, ADJUSTABLE NIPPLE, THREADED -OUTLET UPPER BODY, GRATE AND NEOPRENE -12" (305) DIA-ISOLATION GASKETS. OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIOR PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE. **CERTIFIED FOR:** NONE JOB NAME: \_\_ SHEET: MODEL PMD-FF ISOLATED 6 INCH DRAIN CUSTOMER: FOR FLOATING FLOOR THE VMC GROUP DRAWING NO. REVISION CUSTOMER P.O.: The Power of Together Bloomingdale, NJ 07403 SALES ORDER:

Houston, TX 77041