174R-103047 REV.: 2 DESCRIPTION REV. DATE BY REF. OUTSIDE OF FLASHING -CURB DATA TOTAL CURB WEIGHT: 100 LBS QUANTITY: 1 SHIPPED IN: 1 SECTION(S) **MAX DUCT SIZE -**LOWER RAIL O.A. DIMS... CURB HEIGHT: -1 1/2 MIN. CURB LINEAL FOOTAGE:__ DUCT SUPPLY AIR RETURN AIR **OPENING** OUTSIDE FLASHING OPENING **OPTIONS** YES NO TYP. □ SEISMIC ☐ ISOLATED ☐ DUCT SUPPORT TYP. DUCT SUPPORT OR CROSS BRACE FLUSH TO TOP SPRING NOTE SPRING MAX. RATED MAX. SPRING POCKET IDENT. COLOR LOAD PER DEFL LOCATION POCKET NO. (IN.) 1. ROOFING AND INSULATION TO BE SUPPLIED BY OTHERS. TAG:_ 2. OUTSIDE DIMENSIONS OF CURB MATCH UNIT MANUFACTURERS CURB. MANUFACTURER:___ MODEL NUMBER:__ 3. SEE BULLETIN XXXX FOR TYPICAL INSTALLATION DETAILS AND ADJUSTMENT INSTRUCTIONS. OPERATING WEIGHT:_____ OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIOR 4. FOR MANUFACTURING DETAILS. REFERENCE SUBSEQUENT DRAWING SHEETS. PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE. **CERTIFIED FOR:** NONE JOB NAME: ___ SHEET: MODEL TELECUB CUSTOMER: ISOLATED TELESCOPING CURB THE VMC GROUP DRAWING NO. REVISION CUSTOMER P.O.: The Power of Together Bloomingdale, NJ 07403 SALES ORDER:

Houston, TX 77041